



MS-900 Self-Adhesive Banding Tape with MS1000

Technical Data

Description



MS-900 UV self-adhesive color banding tape is specially designed for outdoor use. It is manufactured from premium grade thermoplastic with a permanent acrylic pressure sensitive adhesive. The film has a UV Overlamine providing not only additional chemical resistance but also excellent UV and fade resistance for extended outdoor durability. Colored banding tape is used to provide line service designations, system color-coding or various labeling needs. Banding tape colors conform to the ASME A 13.1 "Scheme for the Identification of Piping Systems."

- Complies with MIL-SPEC 101C
- Standard sizes: 1" (25 mm) and 2" (51 mm) wide by 50 yds (46 m) long.
- Also available in 3" (76 mm), 4" (102 mm), and 6" (152 mm) rolls.

Physical and Chemical Characteristics

Base Material:	Premium-grade Polyester w/ MS1000 Overlamine	
Material Thickness:	.003" (.076 mm)	
Service Temperature:	-50°F to 250°F (-45°C to 121°C)	
Application Temperature:	+32°F (0°C)	
Chemical Resistance:	Excellent	
Water Resistance:	Excellent	
Expected Outdoor Durability:	Excellent (5 – 8 Years)	
Storage Durability:	Up to 2 Years	
Abrasion Resistance:	Very Good	
Mounting:	Permanent pressure sensitive acrylic adhesive backing	
Finish:	Gloss Surface	
Text Height:	Designed to meet ANSI & ASME Standards (See chart)	
Typical Sizes:	Designed to meet ANSI & ASME Standards (See chart)	
Standard Colors:	Designed to meet ANSI & ASME Standards (See chart)	
Options:	Custom Sizes Available	
Chemical Table:	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good	Acetone: Good Isopropyl Alcohol: Excellent De-Ionized Water: Excellent

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com

Revised 2/5/2025



Designation of Colors (ASME A13.1-2023 & ANSI Z535-2017)

Designation of Colors — ASME A13.1-2023 & ANSI Z535-2017 Standards		
Classification	Color Scheme	
Defined Applications		
Firefighting	White text on red	Sample
Toxic or corrosive	Black text on orange	Sample
Flammable, combustible, or oxidizing	Black text on yellow	Sample
Steam; or steam condensate, boiler feedwater, or other hot water	Black text on gray	Sample
Potable, cooling, or other cold or tepid water	White text on green	Sample
Compressed air	White text on blue	Sample
Undefined Applications		
Defined by user	White text on purple	Sample
Defined by user	Black text on white	Sample
Defined by user	White text on brown	Sample
Defined by user	White text on black	Sample

Designation of Colors (ANSI/ASME A13.1-1996)

Designation of Colors — ANSI/ASME A13.1-1996 Standards		
Classification	Color Scheme	
Materials Inherently Hazardous		
Flammable or Explosive, Chemically Active or Toxic, Extreme Temperature or Pressures, Radioactive	Black text on yellow	Sample
Materials Inherently Low Hazard		
Liquid or Liquid Admixture (non-hazardous materials)	White text on green	Sample
Gas or Gaseous Admixture (non-hazardous materials)	White text on blue	Sample
Fire Quenching Materials		
Water, Foam, CO2, Halon, etc.	White text on red	Sample

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com