



## MS-995 Carrier Ammonia Pipe Markers

### Technical Data



### Description

MS-995 Carrier Pipe Markers are a strap-on type pipe marker consisting of a mechanically applied MS-995 pipe label and two slotted nylon feet. The MS-995 strap-on pipe markers may be used in all applications of piping from 3/4" and greater in outside diameter including insulation. A Type 316 stainless steel banding, either coated or uncoated is recommended.

These carriers are of a universal design, with full length slots on the reverse side to allow for a wide variety of attachment points. The small and large nylon feet are interchangeable depending upon the pipe diameter and client preference. The foot assembly may be strapped to the pipe prior to attaching the carrier or the carrier assembly may be strapped as a unit to the pipe, allowing for maximum installation flexibility.

Flow direction is indicated by a provided separate arrow overlay label of the same material, applied to the carrier when the marker is installed. The UV Overlaminates on the carrier label provides maximum protection against fading due to prolonged exposure to direct sunlight. This also provides excellent resistance to hydrocarbons, acids, and bases. The curved shape reduces the direct constant UV exposure to sunlight and helps longevity and readability. These carrier assemblies have been designed and tested to withstand up to 150 mph sustained wind velocity for one hour, when installed as recommended.

*Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.*

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com

Revised on 2/18/2025



# MS-995 Carrier Ammonia Pipe Markers

## Technical Data

### Physical and Chemical Characteristics

<b>Base Material:</b>	Carrier: Thick co-extruded material   Label: Polyester w/ UV resistant coating
<b>Material Thickness:</b>	Carrier: .100" (2.54mm)   Label: .003" (.076 mm)
<b>Service Temperature:</b>	-40°F to 200°F (-40°C to 94°C)
<b>Application Temperature:</b>	n/a
<b>Chemical Resistance:</b>	Excellent
<b>Water Resistance:</b>	Excellent
<b>Expected Outdoor Durability:</b>	Excellent (7+ Years)
<b>Storage Durability:</b>	Up to 2 Years
<b>Abrasion Resistance:</b>	Very Good
<b>Mounting:</b>	Stainless Steel Strapping
<b>Finish:</b>	Gloss Surface
<b>Text Height:</b>	Designed to meet ANSI/IIAR 2-2021 Appendix Q (see chart)
<b>Typical Sizes:</b>	Designed to meet ANSI/IIAR 2-2021 Appendix Q (see chart)
<b>Standard Colors:</b>	Designed to meet ANSI/IIAR 2-2021 Appendix Q (see chart)
<b>Options:</b>	n/a
<b>Chemical Table</b>	Acid Resistance: Good Alkalis Resistance: Good Salts Resistance: Good

### Marker Sizes and Style

Pipe Diameter (including insulation)	Marker Style (Orange)	Marker Style (Yellow)	Carrier Size	Label Height
3/4" – 1 7/8"	AMAO	AMA	2.2" x 10"	1.5" x 9"
2" – 7 7/8"	AMFO	AMF	3.5" x 17"	2.5" x 16"
Greater than 8"	AMO	AM	5" x 33"	4.5" x 32"

Information on physical and chemical characteristics is based on tests we believe to be reliable. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for their specific application.

8265 N. Faulkner Road, Milwaukee, WI 53224

Ph: 800.234.0135 | Email: sales@markserv.com | Website: www.markserv.com

Revised on 2/18/2025